



Sensor Port
 3/8" Compression gland Standard.
 Available :
 1/8"
 1/4"
 1/2"
 Titanium dry well.

Specifications for Ti-HXF Heat Exchangers (Direct Expansion)

MODEL NO.	NOMINAL HP	REFRIGERATION CONNECTIONS		WATER IN/OUT	Water Flow (GPM)		A	B	C	D
		Liquid	Suction		Min	Max				
Ti-HXF-6	1 1/2-2	1/2"	3/4"	2" SLIP	20	100	36"	19 1/2"	17 1/2"	13 1/2"
Ti-HXF-7	3-4	1/2"	3/4"	2" SLIP	20	100	48"	31 1/2"	17 1/2"	13 1/2"
Ti-HXF-8	5	5/8"	3/4"	2" SLIP	50	150	62"	45 1/2"	17 1/2"	13 1/2"
Ti-HXF-9	7.5	5/8"	3/4"	2" SLIP	50	150	72"	60 1/2"	17 1/2"	13 1/2"

1. Specifications subject to change without notice.
2. Nominal horsepower rating based on 12,000 Btuh @ 70°F water temperature.
3. Dimensions may vary, if size is critical please contact UMI to discuss options.
4. Brass 45° SAE Male Flare Fittings.
5. Flow rate requirements are relative to water temperature. As a rule, colder water requires higher flow rates.

Options: SCH 80 And CPVC material shell construction
 316 SS. or Marine grade Aluminum Mounting frame. (Wall mount, Floor mount or Vertical mount.)
 316 Stainless steel hardware.

UMI
 Universal Marine Industries
 2790 Sunnyside Rd,
 Anmore, BC V3H3C8
 Canada

TITLE:
 Ti-HFX-6 Thru 9 Heat Exchanger

Last Update: 11-27-2009

Date: 11-27-2009

BY: EK